



## **ALL INDIA INSTITUTE OF MEDICAL SCIENCES, BATHINDA**

NEAR GIANI ZAIL SINGH COLLEGE, JODHPUR ROMANA, DABWALI ROAD-151001

### **Invitation of quotation for establishment of a Lactation Management Centre at Neonatology Department, AIIMS Bathinda**

Reference No.: AIIMS Bathinda/Engg. & Estate/26-27/ 5367

Dated: 25 April 2026

*[Handwritten signature]*  
*[Handwritten initials]*

## Notice for Invitation of quotations

**Sealed Quotations** are invited on behalf AIIMS, Bathinda for the subject work at AIIMS Bathinda as per terms & conditions mentioned below. The filled quotations along with all the required documents must reach in the office of the undersigned on or before **05<sup>th</sup> May2026 (Tuesday), 17:00 hrs. (Date & Time)**. The **Envelope containing the quotation** must be sealed and super scribed as under: -

***"Invitation of quotation for establishment of a Lactation Management Centre at Neonatology Department, AIIMS Bathinda - Department of Engineering & Estate"***

The Quotation should be sent to the address: -

The Executive Director  
AIIMS Bathinda,  
Mandi Dabwali Road,  
Punjab - 151001.

### Terms & Conditions:

1. The quotations received **after this deadline or unsealed shall not be entertained** under any circumstances whatsoever. In case of postal delay this Institute will not be responsible. The offer submitted by Fax / email shall not be considered and no correspondence will be entertained in this matter.
2. Quotations must be in the **enclosed prescribed Performa (BoQ) on the letterhead of the firm duly signed** by the Proprietor/ Partner/ Director or their authorized representative, in case of signing of quotation by the authorized representative letter of authorization must be attached with the quotation.
3. The supplier should supply and installed all the items.
4. Rates must be quoted in Indian rupees. Rates must be inclusive of **all charges** (including Freight charges, taxes, etc.). **No overwriting or cutting** is permitted in the rate. If found, the quotation shall be summarily rejected.
5. The **rates quoted must be valid for 90 days minimum from the date of opening of the quotation** and silence of any tendered on this issue shall be treated as agreed with this condition.
6. **Total cost/amount will be taken in consideration for L1.** Becoming L1 will not be the criteria for awarding of purchase order unless the rates are reasonable & justified.
7. The firm/agency may satisfy the following conditions: -
  - (i) The firm shall have valid GST/Other taxes and IT PAN.
  - (ii) The firm should not be black listed by any Government agency/Department.
8. Quantity may increase or decrease as per the decision of the competent authority of AIIMS Bathinda.



9. **Work Completion period** - within 15 days from Purchase order or as per work order awarded.
10. **Payment Terms:** Payment will be only after satisfactorily execution of the work and after inspection by the AIIMS Bathinda. Payment will be done after verification of the work done by the engineering wing. No advance payment shall be admissible.
11. Unsealed quotations, quotations received after due date, quotations not super scribed as mentioned above, unsigned quotations are liable to be rejected. No queries regarding the same shall be entertained in this office. Quotations received through email, fax, telegram etc. shall not be entertained.
12. The decision of AIIMS Bathinda on all matters concerning this work shall be final and binding on the party submitting the quotation.
13. **Defect Liability Period:** DLP shall be of 03 month from completion date of the work.
14. To ensure the compliance during the **DLP period, 05% of the amount shall be withheld** from each bill of the contractor and that will be released after completion of the DLP period.
15. If the contractor does not start the work within the scheduled time, the contractor shall be debarred from participating in future tender of the Institute as per the respective clause of the Manual for Procurement of Works.
16. The work shall required to be executed as per the CPWD specifications. Substandard material/ work shall be rejected. Replacement of the same be done within 03 days from the issue of the notice, otherwise the contractor shall be liable to be penalized.
17. **LIQUIDATED DAMAGES:** - The successful bidder must start the work within 7 days of issuance of Letter of Commencement of work and complete the work within the time frame as stipulated by the AIIMS Bathinda, failing which, AIIMS Bathinda will recover Compensation for Delay of work @ .5 % per week or part of the week of delayed of the total amount of work (accepted Tendered Value of work) which may be recovered from bill/Performance Security/Security Deposit of the contractor. The total amount of compensation for delay to be paid under this condition shall not exceed 5 % (Five percent) of the Accepted tendered value of work. The said work can also be executed under the Risk and Cost of the Contractor with prior intimation of 15 days based upon the performance of the contractor.
18. **STATUTORY DEDUCTIONS:** - All the statutory deductions towards GST/Income Tax etc. shall be made from the bill/s as applicable as per the prevailing rates under the rules. TDS as applicable will be deducted from each bill of the contractor under the statutory rules of the Union Govt., in respect of Income Tax and other taxes. No claim on account of any other

statutory charges for execution of work awarded under this contract will be entertained by AIIMS Bathinda and such charges should be paid by the contractor himself.

19. **INDEMNIFICATION:** - AIIMS Bathinda shall have no liability whatsoever towards the persons deployed by the contractor for the subject of work. The contractor shall keep AIIMS Bathinda indemnified against all losses/damages/liabilities/claims arising out of deployment of the contractor's workers during the period of the contract. Any claim which may arise during the currency of the contract or at any subsequent point of time shall be the sole responsibility of the contractor and AIIMS Bathinda shall in no way be held responsible for it.

20. **LIABILITY AGAINST LOSS OR DAMAGE TO LIFE OR PROPERTY:** - The contractor shall be liable to pay AIIMS Bathinda for any loss/damage caused because of theft/pilferage of any property of AIIMS Bathinda from the premises where the staffs of the contractor have been deployed, provided such loss/damage is due to the negligence of the contractor or its deployed manpower which shall be deducted from Security deposit/Performance Guarantee if not paid. The contractor shall also be liable for the consequences of any incident of major/minor injury or accident or death caused to any of its worker arising out of or in the course of his employment under the scope of the contract. AIIMS Bathinda shall not be responsible for any injury or loss of life in respect of the contractor that may take place while on work. Any compensation or expenditure towards treatment for such injury or loss of life shall be the sole responsibility of the contractor. The contractor shall be solely responsible for any damage, injury or accident that may occur to any of his personnel working under his contract. No claim whatsoever arises to AIIMS Bathinda.

  
Asst. Engineer (Civil)  
AIIMS Bathinda

  


**Check List**

| <b>S. No.</b> | <b>Particulars</b>   | <b>Whether attached</b> | <b>Remarks</b> |
|---------------|--|-------------------------|----------------|
| 1             | GST certificate  | YES / NO                |                |
| 2             | PAN Card   | YES / NO                |                |
| 3             | Non-Blacklisting Undertaking on letter head  | YES / NO                |                |
| 4             | All the documents mentioned above and the quotation document has been signed & stamped | YES / NO                |                |

  
Reeb

## BOQ

| S.no | Description   | unit | Quantity | Rate | Amount |
|------|---|------|----------|------|--------|
| 1    | Providing and fixing Aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/appropriate Z sections and other sections of approved make conforming to IS:733 and IS:1285. Fixing with dash fasteners of required dia and size including necessary filling up the gaps at junctions ie, at top, bottom and sides with required EPDM rubber/neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, aluminium snap beading for glazing/ panelling, C.P. brass/stainless steel screws, all complete as per architectural drawings and directions of Engineer-in-charge. (Glazing, panelling and dash fasteners to be paid separately.) |      |          |      |        |
|      | For shutters of doors, windows & ventilators including providing and fixing hinges/pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber/neoprene gasket required (Fittings shall be paid for separately)  |      |          |      |        |
|      | Powder coated aluminium (minimum thickness of powder coating 50 micron)   | Kg   | 110      |      |        |
| 2    | For fixed portion.  |      |          |      |        |
|      | Powder coated aluminium (Minimum thickness of powder coating 50 micron)   | Kg   | 250      |      |        |
| 3    | Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc, with EPDM rubber/ neoprene gasket etc. complete as per the architectural drawings and the directions of Engineer-in charge. (Cost of aluminium snap beading shall be paid in basic item) With float glass panes of 5mm thickness.   |      |          |      |        |
|      | With float glass panes of 5 mm thickness (weight not less than 12.50 kg/sqm)  | Sqm  | 26       |      |        |
| 4    | Providing and fixing aluminium round shape handle of outer dia 100 mm with SS screws etc. complete as per direction of Engineer-in-charge   |      |          |      |        |
|      | Powder coated minimum thickness 50 micron aluminium   | Each | 12       |      |        |
| 5    | Providing and fixing aluminium die cast body tubular type universal hydraulic door closer (having brand logo with ISI, IS : 3564, embossed on the body, door weight upto 35 kg and door width upto 700 mm), with necessary accessories and screws etc. complete.  | Each | 6        |      |        |
| 6    | Providing and fixing bright finished 100 mm mortice lock with 6 levers without pair of handles of approved quality for aluminium door, with necessary screws etc complete as per direction of Engineer- in-charge.  | Each | 3        |      |        |
| 7    | Providing & Fixing decorative high pressure laminated sheet of plain / wood grain in gloss / matt/ suede finish with high density protective surface layer and reverse side of adhesive bonding quality conforming to IS : 2046 Type S, including cost of adhesive of approved quality.   |      |          |      |        |
|      | 1.0 mm thick  | Sqm  | 50       |      |        |

*Handwritten signature and initials*

|    |  |      |    |  |  |
|----|--|------|----|--|--|
| 8  | Providing and fixing stainless steel soft closing spring hinges at 0 degree hinges (hydraulic type) of approved make/brand to cupboard shutters with full threaded steel screws including making necessary recess in board and finished etc. complete as per direction of Engineer-in-charge.  | Each | 10 |  |  |
| 9  | Providing and fixing stainless steel fancy handle of approved make fixed with SS screws etc. complete as per direction of Engineer-in-charge.  |      |    |  |  |
|    | 200 mm   | Each | 10 |  |  |
| 10 | Providing and fixing factory made single extruded WPC (Wood Polymer Composite) solid board one side white color and other side of board laminated with PVC foil of minimum 14 micron thickness of approved design pasted with hot melt adhesive for cup boards, work stations and bathroom/kitchen cabinet etc. of required sizes comprising of virgin polymer of K value 58-60 (Suspension Grade), calcium carbonate and natural fibers (wood powder/ rice husk/wheat husk) and non toxic additives (maximum toxicity index of 12 for 100 gms) having minimum density of 650 kg/cum and screw withdrawal strength of 1800 N (Face) & 900 N (Edge), minimum compressive strength 50 N/mm <sup>2</sup> , modulus of elasticity 850 N/mm <sup>2</sup> and resistance to spread of flame of Class A category with property of being termite/borer proof, water/moisture proof and fire retardant and fixing with stainless steel piano hinges/soft close clip on concealed hinges of required size with necessary full body threaded star headed counter sunk S.S screws, all as per direction of Engineer-In- Charge. (Note: stainless steel piano hinges/soft close clip on concealed hinges and necessary S.S screws shall be paid separately) |      |    |  |  |
|    | 18 mm thick  | Sqm  | 25 |  |  |
| 11 | White Vitreous China Wash basin size 630x450 mm with a pair of 15 mm C.P. brass pillar taps  | Nos  | 2  |  |  |
| 12 | Providing and fixing P.V.C. waste pipe for sink or wash basin including P.V.C. waste fittings complete.  |      |    |  |  |
|    | Flexible pipe  |      |    |  |  |
|    | 32 mm dia  | each | 4  |  |  |
| 13 | Providing and fixing aluminium hanging floor door stopper, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade, with necessary screws etc. complete.   |      |    |  |  |
|    | Single rubber stopper  | each | 6  |  |  |
| 14 | Steel reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete upto plinth level.   |      |    |  |  |
|    | Thermo-Mechanically Treated bars of grade Fe-500D or more.   | Kg   | 20 |  |  |
| 15 | Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level.   |      |    |  |  |
|    | Cement mortar 1:3 (1 cement :3 coarse sand)  | Sqm  | 7  |  |  |

*[Handwritten signature]*  
*[Handwritten initials]*

|   |  |      |      |  |                    |
|---|--|------|------|--|--------------------|
| 16  | Providing and laying in position ready mixed or site batched design mix cement concrete for reinforced cement concrete work; using coarse aggregate and fine aggregate derived from natural sources, Portland Pozzolana / Ordinary Portland /Portland Slag cement, admixtures in recommended proportions as per IS: 9103 to accelerate / retard setting of concrete, to improve durability and workability without impairing strength; including pumping of concrete to site of laying, curing, carriage for all leads; but excluding the cost of centering, shuttering, finishing and reinforcement as per direction of the engineer-in-charge; for the following grades of concrete.<br>Note: Extra cement up to 10% of the minimum specified cement content in design mix shall be payable separately. In case the cement content in design mix is more than 110% of the specified minimum cement content, the contractor shall have discretion to either re-design the mix or bear the cost of extra cement. |      |      |  |                    |
|   | All works above plinth level upto floor V level  |      |      |  |                    |
|   | Concrete of M25 grade with minimum cement content of 330 kg /cum   | cum  | 0.85 |  |                    |
| 17  | Centering and shuttering including strutting, propping etc. and removal of form for  |      |      |  |                    |
|   | Shelves (Cast in situ)   | Sqm  | 7    |  |                    |
| 18  | Providing and laying gang saw cut 18 mm thick, mirror polished pre moulded and pre polished machine cut granite stone of required size and shape of approved shade, colour and texture in footpath, flooring cut granite stone of required size and shape of approved shade, colour and texture in footpath, flooring in road side plazas and similar locations, laid over 20mm thick base of cement mortar 1:4 (1cement : 4 coarse sand) including grouting the joints with white cement mixed with matching pigment, epoxy touch ups etc. complete as per direction of Engineer-in-Charge.   |      |      |  |                    |
|   | With granite stone of area less than 0.50 sqm.   | Sqm  | 6    |  |                    |
| 19  | Providing and fixing 12 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge   |      |      |  |                    |
|   | Pre-laminated particle board with decorative lamination on both sides  | Sqm  | 25   |  |                    |
| 20  | Providing and fixing aluminium tower bolts, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868 ) transparent or dyed to required colour or shade, with necessary screws etc. complete :   |      |      |  |                    |
|   | Providing and fixing of Oxidised mild steel tower bolt (barrel type) 150x10 mm   | Each | 6    |  |                    |
|   |  |      |      |  | <b>Total</b>       |
|   |  |      |      |  | <b>GST @ 18%</b>   |
|   |  |      |      |  | <b>Grand Total</b> |
| <b>NOTE: The rates shall inclusive of supply of the material and transportation charges</b> |  |      |      |  |                    |